



# ME2 | SATA | 2.5" SSD

SMART's ME2 SATA 2.5" SSDs incorporate the latest generation 3D NAND-technology and SMART Modular's proprietary NVMSentry™ firmware to deliver high performance SSD products with endurance up to one drive writes per day (1 DWPD) for five years. The new ME2 SSDs offer better cost per bit over previous 64-layer and 96-layer NAND generations without sacrificing performance and reliability. Further optimization of the NVMSentry firmware also yields enhancements in read and write consistency over wide ranges of application workloads.

SMART's ME2 SATA 2.5" SSDs are available in both industrial and commercial temperature grades and have versions that implement SMART's SafeDATA™ power-loss, data-protection technology for graceful handling of power fluctuations and sudden power loss events.



## Features & Benefits

- The Latest Generation 3D NAND Technology
- Quality of Service (QoS) with 3 Nines of Latency Consistency
- 1 DWPD For Five Years
- SMART's Proprietary NVMSentry Firmware
- SafeDATA Power-Loss, Data-Protection Technology
- TCG OPAL 2.0 and AES 256 Encryption
- End-to-End Data Path Protection
- Support I-Temp (-40°C to +85°C)

## Applications

- AI
- Data Center
- Industrial
- Networking
- Surveillance

## Product Family Overview

Form Factor	Capacity	Sequential Performance
2.5" SSD	240GB to 1920GB	
M.2 2242 SSD	240GB to 960GB	
M.2 2280 SSD	240GB to 1920GB	Up to 540MB/s Read
mSATA SSD	240GB to 1920GB	Up to 460MB/s Write
Slim SATA SSD	240GB to 1920GB	

## Specifications

ME2   SATA   2.5" SSD	
NAND Type	eTLC
<b>Performance</b>	
Host Interface Rate (maximum)	SATA 3.0 6Gb/s
Capacities	240GB to 1920GB
Sequential Read (maximum)	Up to 540 MB/s
Sequential Write (maximum)	Up to 460 MB/s
Random Read (maximum)	Up to 77K IOPS
Random Write (maximum)	Up to 70K IOPS
<b>Reliability</b>	
MTBF	> 2,000,000 hours
	1920GB: 3755 TBW
Endurance	960GB: 2275 TBW
(JEDEC Enterprise Workload) <sup>1</sup>	480GB: 1015 TBW
	240GB: 510 TBW
DWPD	1
SafeDATA	Optional
Error Correction	LDPC
<b>Data Security</b>	
Encryption	AES-256, TCG OPAL 2.0
<b>Power</b>	
Input Voltage	VCC: 5 V ± 10%
<b>Environmental</b>	
Shock	1500 g half-sine, 0.5 msec, 1 shock along each axis, X, Y, Z in each direction
Vibration	20G rms 80-2000Hz, 1.52mm 20-80Hz, 3 axis
Operating Temperature	Commercial: 0°C to +70°C Industrial: -40°C to +85°C
Storage Temperature	-40°C to +85°C
Humidity	40°C, Operation: 90% RH, Storage: 93% RH
<b>Physical</b>	
Length	100 mm
Width	69.85 mm
Height	7 mm

<sup>1</sup>Endurance is directly related to the User Specific Workload.

## Ordering Information

Part Number	Density
<b>ME2   SATA   2.5" SSD</b>	
<b>Commercial Operating Temperature (0°C to +70°C)</b>	
SRS251920FCM2BC3	1920GB
SRS25960GFCM2BC3	960GB
SRS25480GFCM2BC3	480GB
SRS25240GFCM2BC3	240GB
<b>ME2   SATA   2.5" SSD</b>	
<b>Industrial Operating Temperature (-40°C to +85°C)</b>	
SRS251920FIM2BC3	1920GB
SRS25960GFIM2BC3	960GB
SRS25480GFIM2BC3	480GB
SRS25240GFIM2BC3	240GB
<b>ME2   SATA   2.5" SSD (SafeDATA)</b>	
<b>Commercial Operating Temperature (0°C to +70°C)</b>	
SRS251920F1M2AC3	1920GB
SRS25960GF1M2AC3	960GB
SRS25480GF1M2AC3	480GB
SRS25240GF1M2AC3	240GB
<b>ME2   SATA   2.5" SSD (SafeDATA)</b>	
<b>Industrial Operating Temperature (-40°C to +85°C)</b>	
SRS251920F2M2AC3	1920GB
SRS25960GF2M2AC3	960GB
SRS25480GF2M2AC3	480GB
SRS25240GF2M2AC3	240GB



For more information, please visit: [www.smartm.com](http://www.smartm.com)

*\*Product images are for promotional purposes only. Labels may not be representative of the actual product.*

### Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231  
F: (+1) 510-623-1434 • E: [info@smartm.com](mailto:info@smartm.com)

### Latin America:

T: (+55) 11 4417-7200 • E: [sales.br@smartm.com](mailto:sales.br@smartm.com)

### Asia/Pacific:

T: (+65) 6678-7670 • E: [sales.asia@smartm.com](mailto:sales.asia@smartm.com)

### EMEA:

T: (+44) 0 7826-064-745 • E: [sales.euro@smartm.com](mailto:sales.euro@smartm.com)

### Customer Service:

T: (+1) 510-623-1231 • E: [customers@smartm.com](mailto:customers@smartm.com)