

DDR5 VLP RDIMM

SMART Modular Technologies' DDR5 VLP RDIMM. The 32GB VLP RDIMM is targeted for embedded 1U blade compute and storage applications, enterprise networking and telecom applications, and industrial single board computers (SBCs). Its main attributes are VLP height, high density for a VLP module, and high DDR5-4800 performance.

SMART's DuraMemory DDR5 32GB VLP RDIMM is the industry's first DDR5 VLP RDIMM form factor. For ruggedized and harsh operating conditions, SMART offers retention clips to secure the socket latches in place and industrial grade temperature operation (-40°C to +85°C).

The 32GB VLP RDIMM is the newest product added to SMART's wide portfolio of VLP and ULP (Ultra Low Profile) modules that target all type of very dense computing, storage, networking and telecom applications.

Features & Benefits

- VLP RDIMM height of 18.75mm allows for vertical DIMM placement in 1U blades to save board space
- High density can achieve up to 384GB in 1U compute and storage blade systems with 12 DIMM sockets
- High performance DDR5-4800 operation



Applications

- Networking and Telecom
- Industrial, Computing, and Storage
- ATCA Blades

Ordering Information

288-PIN - DDR5 VLP RDIMM							
SMART Part Number	Density	Height (mm)	Module Config	Comp Config	Speed	Voltage	Temp*
SR6G8RD5388HMV	48GB	18.75	4Gb x80	3Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G8RD5288HAV	32GB	18.75	4Gb x80	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G8RD5288SBV	32GB	18.75	4Gb x80	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G8RD5288MDV	32GB	18.75	4Gb x80	2Gx8	5600MT/s	1.1V	0°C to +70°C
SR4G8RD5285SBV	32GB	18.75	4Gb x80	2Gx8	4800MT/s	1.1V	0°C to +70°C
SR4G8RD5285HAV	32GB	18.75	4Gb x80	2Gx8	4800MT/s	1.1V	0°C to +70°C

* Reflects Operating Ambient Temperature



For more information, please visit: www.smartm.com

*Product images are for promotional purposes only. Labels may not be representative of the actual product.

EMEA:

Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231 F: (+1) 510-623-1434 • E: info@smartm.com T: (+55) 11 4417-7200 • E: sales.br@smartm.com

Asia/Pacific:

Latin America:

T: (+65) 6678-7670 • E: sales.asia@smartm.com

T: (+44) 0 7826-064-745 • E: sales.euro@smartm.com

Customer Service: T: (+1) 510-623-1231 • E: customers@smartm.com

©2024, SMART Modular Technologies, All rights reserved. The stylized "S" in conjunction with "SMART", as well as "SMART Modular Technologies" are registered trademarks of SMART Modular Technologies. All other trademarks are the property of the respective owners. These materials are provided by SMART Modular Technologies as a service to its customers and may only be used for informational purposes. 10.06.24/DDR5_RDIMM/Rev.18