



# SMART RUGGED™

## T6EN | PCIe/NVMe U.2, M.2 and E1.S

SMART's RUGGED™ T6EN U.2, M.2 2280 and E1.S PCIe/NVMe Gen4x4 solid state drives (SSDs) deliver high performance, high capacity storage solutions optimized for defense, aerospace and other applications requiring durable, rugged and secure storage.

Powered by a flexible, custom flash controller, T6EN SSDs provide sustained read/write performance to meet the needs of high throughput applications such as flight data recorders and sensor data capture. T6EN SSDs are also well suited for high-reliability telemetry, surveillance, and mission critical applications.

T6EN U.2 SSDs provide capacities up to 15360GB and the M.2 & E1.S up to 7680GB. They are more reliable, offer superior performance, and require less power and cooling than traditional hard disk drives (HDDs). T5EN drives provide power fail protection (U.2 and E1.S only).

### Features & Benefits

- AES-XTS 256-bit encryption automatically protects all data written to the drive
- OPAL 2.0 compliant
- True industrial grade storage solution for “no-compromise” applications
- Advanced flash management for enhanced reliability and durability
- Self-Monitoring Analysis and Reporting Technology (S.M.A.R.T.) support
- 100% 8 hour burn-in over Temperature (-40°C to +85°C, I-Temp Version)
- SafeDATA™ technology is a standard feature that safeguards the integrity, functionality and data of the SSD in the event of sudden power loss

### Product Family Overview

Capacity	Sequential Performance	Random Performance
960GB to 15360GB	Up to 3,500 MB/s Read Up to 3,200 MB/s Write	390,000 IOPS Read 55,000 IOPS Write

One gigabyte, or GB, equals one billion bytes when referring to drive capacity. Accessible capacity may vary based on the operating environment and drive formatting



### Applications

- Defense
- Aerospace
- Flight Data Recorders
- Sensor Capture
- Telemetry
- Surveillance

## Specifications

	E1.S	U.2	M.2 2280
<b>NAND Type</b>	TLC		
<b>Compliance</b>			
PCIe	Gen 4 x4		
<b>Performance</b>			
Sequential Read MB/s	Up to 3,500	Up to 3,500	Up to 3,200
Sequential Write MB/s	Up to 3,000	Up to 3,000	Up to 3,200
Random Read (4KB) IOPS	Up to 390,000	Up to 390,000	Up to 390,000
Random Write (4KB) IOPS	Up to 55,000	Up to 55,000	Up to 50,000
<b>Capacity</b>			
3D-TLC <sup>1</sup>	960GB–7680GB	960GB–15360GB	960GB–7680GB
<b>Reliability</b>			
MTBF <sup>2</sup>	> 2M hours, Telcordia 20°C		
Data Reliability	1 in 10 <sup>17</sup> bits read		
Data Retention	> 10 years @ 25°C		
Endurance <sup>3</sup>	I-Temp: 9,600 TBW (with 15,360GB)		
Warranty	1 Year		
<b>Power</b>			
Input Voltage	12.0V ± 10%	12.0V ± 10%	3.3V ± 5%
Idle (typical)	< 1.5 W	< 1.5 W	< 1.5 W
Operational (typical)	< 9.0 W	< 9.0 W	< 9.0 W
<b>Environmental</b>			
Operating Shock	50G, (11ms duration, half sine wave)		
Vibration	10G(Peak, 10~2000Hz)		
Altitude	24,384m [80,000 ft.]		
Relative Humidity	5% to 95% non-condensing		
Conformal Coating	Optional		
Operating Temp	Industrial (-40°C to 85°C)		
Storage Temp	-55°C to 90°C		
<b>Mechanical</b>			
Length	18.75mm	100.5mm	80mm
Width	33.75mm	69.85mm	24mm
Height	9.5mm	7mm	11.6mm
Connector	E1.S	U.2	M.2 M-Key

(1) One gigabyte, or GB, equals one billion bytes when referring to drive capacity. Accessible capacity may vary based on the operating environment and drive formatting  
 (2) Based on 480GB drive  
 (3) Under typical conditions

## Data Security Features

	U.2 PCIe/NVMe
Encryption	AES-XTS 256-bit (FIPS 197 compliant)
Key Management	TCG Opal 2.0
Elimination	ATA-8 Security Erase DoD NISPOM 5220.22-M DoD NISPOM 5220.22-M-Sup 1 NSA/CSS Manual 130-2 NSA/CSS Manual 9-12 Army AR 380-19 Navy NAVSO P-5239-26 Air Force AFSSI-5020 External trigger
Write Protect	Hardware Write Protect

## U.2 Ordering Information

Part Number	Density
<b>I-Temp TLC</b>	
HRCN7P15360ME001*	15360GB
HRCN7P7680ME001*	7680GB
HRCN7P3840HI001*	3840GB
HRCN7P1920HI001*	1920GB
HRCN7P0960HI001*	960GB

\*Conformal Coat Option Replace "001" with "CC1"

## M.2 2280 Ordering Information

Part Number	Density
<b>I-Temp TLC</b>	
HRCN3P7680MI001*	7680GB
HRCN3P3840MI001*	3840GB
HRCN3P1920HI001*	1920GB
HRCN3P0960HI001*	960GB

\*Conformal Coat Option Replace "001" with "CC1"

## E1.S Ordering Information

Part Number	Density
<b>I-Temp TLC</b>	
HRCN3P7680MI001*	7680GB
HRCN3P3840MI001*	3840GB
HRCN3P1920HI001*	1920GB
HRCN3P0960HI001*	960GB

\*Conformal Coat Option Replace "001" with "CC1"



For more information, please visit: [www.smartm.com](http://www.smartm.com)

\*Product images are for promotional purposes only. Labels may not be representative of the actual product.

### Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231  
 F: (+1) 510-623-1434 • E: [info@smartm.com](mailto:info@smartm.com)

### Latin America:

T: (+55) 11 4417-7200 • E: [sales.br@smartm.com](mailto:sales.br@smartm.com)

### EMEA:

T: (+44) 0 7826-064-745 • E: [sales.euro@smartm.com](mailto:sales.euro@smartm.com)

### Asia/Pacific:

T: (+65) 6678-7670 • E: [sales.asia@smartm.com](mailto:sales.asia@smartm.com)

### Customer Service:

T: (+1) 510-623-1231 • E: [customers@smartm.com](mailto:customers@smartm.com)